

# FIREwave®

## RSM-CP Wireless Resettable Manual Call Point



### Features

- ▶ Bi Directional wireless communication
- ▶ Fully intelligent
- ▶ Utilises standard low cost lithium battery technology
- ▶ Long battery life
- ▶ Resettable Element
- ▶ Clear 'device activated' warning flag
- ▶ High reliability
- ▶ Automatic channel hopping
- ▶ Self optimising wireless amplitude and frequency
- ▶ Weatherproof version available

### Description

A Wireless Resettable Manual Call Point which features a simulated glass front. When activated, a plastic 'flag' is displayed in the window of the unit; the supplied key will reset the flag and unit. Supplied with back box.

Weatherproof version also available (RSM-CP/W).

### Specification

Ordering code	RSM-CP (internal) RSM-CP/W (external)
Communication range with the Translator Module	150M (open space)
Operating frequency	868-870 MHz
Modulation type	Frequency Shift Keying
Number of operating channels	7
Time period between wireless signal transmissions	From 12 seconds to 2 minutes
Power supply	Batteries
	Capacity
	Estimated battery life*
Operating temperature range	(dual 3V lithium batteries) 1 x Primary Cell (CR123A) 1 x Secondary Cell (CR2032A) 1.2 Ahr 0.24 Ahr 5 years (primary) 2 months (secondary)
Radiated power	-30 °C to +50 °C
Dimensions (mm)	0.01 - 10 mW 87 x 58

\* (dependant on time period between wireless signal transmissions)