

# Surface Wiring Adaptor

## Model YBD-RA



### Features

- ▶ Compatible with the majority of existing Analogue and Conventional bases
- ▶ Colour matches standard Hochiki Analogue and Conventional sensor/detector/base ranges
- ▶ 4 pre-moulded knock-outs provide wiring entry
- ▶ Low profile - only 16mm

### Description

The YBD-RA Surface Wiring Adaptor allows the majority of Hochiki Sensors/Detectors and their Mounting Bases to be fitted flush against a fixing surface whilst also allowing surface wiring (without conduit) to be connected.

The adaptor features four 9mm x 8mm knock-outs for cables/wires allowing surface-fixed wiring to be connected to an appropriate mounting base (depending on application). The adaptor is moulded in ivory white ABS as standard, which allows seamless integration with the majority of mounting bases and associated sensors and detectors.

| Specification                            |                                  |
|--|----------------------------------|
| Ordering Code                            | YBD-RA<br>YBD-RA(WHT)            |
| Maximum Humidity                         | 95%RH - Non Condensing (at 40°C) |
| Colour                                   | Ivory White                      |
| Weight (g) / Diameter (mm) / Height (mm) | 27 / 110 / 16                    |
| Fixing Centres (mm)                      | 61 ~ 89                          |
| Maximum Wire Thickness                   | 2.5mm <sup>2</sup> Cables        |