

Detector Tester

TESTIFIRE



Features

- ▶ Faster, more productive testing with just one tool
- ▶ Simultaneous stimuli (smoke and heat) can cut test times in multi-sensors by up to 66%
- ▶ Stimuli capsules for smoke and CO held within unit
- ▶ Powered by battery batons within pole
- ▶ Clearing cycle provides rapid detector reset with no repeat alarm
- ▶ Heat detector test times reduced through enhanced deployment of heat and wider range of temperature settings

Description

Testifire is a technologically advanced, fully portable device for functional testing of fire detectors. The unit is suitable for testing optical/photoelectric and ionisation smoke sensors, thermal sensors (fixed temperature or rate-of-rise), and carbon monoxide (CO) fire sensors, be they conventional, addressable or analogue addressable. Testifire is also the first functional tester that enables testing of multi-sensors or multi-criteria detectors from a single test unit.

Specification

Ordering code	Testifire 1000 (smoke & heat) Testifire 2000 (smoke, heat & CO) TS3 Capsule (smoke) TC3 Capsule (CO)		
Power Source	Battery Baton: nominal 7.2 V 2.2 Ah NiMH rechargeable battery pack with internal overcurrent protection		
Battery Charge Time	75 to 90 mins (when completely discharged)		
Test Modes	<p>Normal Heat: for heat detectors up to 90 °C Hi Heat: for heat detectors up to 100 °C Smoke: for smoke detectors using a simulated smoke Carbon Monoxide (CO): CO is generated internally and blown into the detector at a concentration of approximately 100ppm (not calibrated). Simultaneous Testing: Smoke, Heat and CO (if appropriate) in any combination as programmed by the user are all carried out in one test. Sequential Testing: Tests are performed according to the order that they have been programmed by the user. Clearing: Clean air is blown to remove previously applied Smoke or CO.</p>		
Operating temperature range	+5 °C to +45 °C		
Storage temperature range	-10 °C to +50 °C		
Maximum humidity	85% RH - Non condensing (at 40 °C)		
Weight (kg) and Dimensions (mm)	Testifire 1000	0.75	W153 x H224 (397 inc handle)
	Testifire 2000	0.9	W153 x H273 (397 inc handle)
	Battery Baton™	0.5	

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.