

# CDXconventional



## CCP-E-IS

### INTRINSICALLY SAFE CONVENTIONAL CALL POINT

#### Features

- ▶ Supports either a 'Frangible' glass element or a 'Non Frangible' plastic element
- ▶ Terminals can accommodate up to a 2.5 mm<sup>2</sup> solid conductor
- ▶ Approved to EN54 Part 12
- ▶ Rugged design
- ▶ ATEX Classification to II 1G EEx ia IIC T4
- ▶ SIL Level 2 capable variant available
- ▶ Flush-fitted. Requires SR-BACKBOX if surface mounting required (sold separately).



#### Description

The CCP-E-IS is a conventional call point based upon the industry standard KAC world series housing, and which can be used in hazardous areas.

#### Specification

Ordering Code	CCP-E-IS
Operating Voltage	15 – 30 VDC
Operating Temperature Range	-10 °C to + 55 °C
Storage Temperature Range	-30 °C to + 70 °C
ATEX Classification	II 1 G EEx ia II T4
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Ingress Protection Rating	IP24
Colour / Case Material	Red / Polyphenylene Oxide
Weight (g) / Dimensions (mm)	(Flush Unit) 93 / W88 x H88 x D20
	(With Surface Mount Back Box) 173 / W88 x H88 x D52



For further information visit [www.hochikieurope.com/is](http://www.hochikieurope.com/is)

Hochiki Europe (UK) Ltd. Reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. To be a complete and up-to-date description. Check online for current version at [store.hochikieurope.com](http://store.hochikieurope.com)