

# CCP-KS

## CONVENTIONAL KEY SWITCH MANUAL CALL POINT

### Features

- ▶ Approved to EN54-11:2001
- ▶ Two position keyswitch (marked “1” and “0”) with key removable in both positions
- ▶ Terminals can accommodate up to a 2.5 mm<sup>2</sup> solid conductor
- ▶ Supplied in RED - other colours available on request
- ▶ Supplied with back box for surface fixing
- ▶ Suitable for fire, security and other specialist applications
- ▶ Approved by LPCB



### Description

The CCP-KS is a Conventional key switch manual call-point based upon the industry standard KAC 9000 series housing and features flying leads for simple wiring.

The unit features two key positions marked as “1” and “0” – with the key easily removable in either position.



### Specification

Ordering codes	CCP-KS
Maximum voltage	240 V ac or 24 V dc
Current rating	2 A @ 240 V ac, 6 A @ 24 V dc
Ingress Protection Rating	IP24D
Operating Temperature Range	-20 °C to +55 °C
Storage Temperature Range	-20 °C to +55 °C
Maximum Humidity	95%RH - Non condensing (at 40 °C)
Colour / Case Material	Red/ABS
Weight (g) / Dimensions (mm)	180 / W87 x H87 x D52