

YBN-R/3M(SCI)

Marine Approved Short-Circuit Isolator Base

Your Safety, Our Technology

Features

- Features integral SCI
- Easy to fit
- Slim profile
- Matches standard base colours



Description

Model YBN-R/3M(SCI) is a sensor mounting base featuring an integral short-circuit isolator which will detect and isolate short-circuits on the loop. When a short-circuit is detected during power up the unit will drop the power to the rest of the loop.

The YBN-R/3M(SCI) is compatible with the ESP range of Marine-Approved sensors and does not require a loop address. A remote fire LED facility is provided when a sensor is attached to the base.

NOTE: A fitted sensor will still be powered when this device is isolating.

Specification

| | |
|--|--|
| Ordering codes | YBN-R/3M(SCI) - Ivory, YBN-R/3M(WHT)-SCI - White |
| Protocol | ESP |
| Operating Voltage | 17 - 41 VDC (24 VDC nominal) |
| Standby current | 60 μ A |
| Current drawn by isolator during fault condition | < 4 mA |
| Maximum current consumption from remote LED | 10 mA (limited by attached sensor) |
| Maximum continuous current | 1 A |
| Maximum quantity per loop | 127*1 |
| Ambient temperature range | -10 °C to +50 °C |
| Relative humidity | 10% to 95% RH (at 40°C) |
| Colour and case material | Ivory or White ABS |
| Fixing centres | 48 mm through to 74 mm |
| Maximum wire thickness | 2.5 mm ² /terminal |
| Weight | 79 g |
| Approvals | DNV |

*1 Check with Fire alarm control panel manufacturer for maximum loop quantities

See AP0127 for short-circuit isolator specifications

Ordering Codes

Product

Marine Approved Short-Circuit Isolator Base - ivory
Marine Approved Short-Circuit Isolator Base - white

Part Number

YBN-R/3M(SCI)
YBN-R/3M(WHT)-SCI