





Marine SCI Sensor Mounting Base

Features

- ▶ Electronics free
- ▶ Stainless steel contacts
- ▶ Takes 2.5mm² cables
- ▶ Slim profile only 8 mm
- ▶ Rugged wiring contacts
- ▶ Facility for remote indicator
- ▶ Quick connection via square cable clamps
- ▶ Also available in white
- ▶ Fourth terminal allows for SCI functionality of sensors
- ▶ Also available in white.



Description

Model YBV-R/4 is a Marine SCI Sensor Mounting Base, which is fully compatible with Hochiki's ESP range of SCI sensors. It is supplied with square cable clamps for secure and reliable cable termination and is also capable of driving a remote

LED if required.

Please note, this base does not provide short-circuit isolation on its own, but allows the SCI sensor range to operate with SCI functionality.

Specification	
Ordering codes	YBV-R/4M - Ivory / YBV-R/4M(WHT) - White
Operating temperature range	-10 °C to +50 °C
Storage temperature range	-30 °C to + 70 °C
Maximum humidity	95% RH - Non Condensing (at 40 °C)
Colour / Material	Ivory or White / ABS
Weight (g) / Diameter (mm) / Height (mm)	50 / 100 / 8
Fixing centres (mm)	48 ~ 74
Maximum wire thickness	2.5 mm² Cables









